IPMX & Live Production

Andrew Starks






















What does Pro AV mean?





The market for audiovisual (AV) communication equipment used in professional, industrial, commercial, and retail environments to communicate with people.

We're all just video now...




IPSHOWCASE

Currently in Pro AV...



- Excellent Quality
- Low latency
- Stable Operation
- ...and incompatible
- Discovery
- Connection
- Transport



Built on Existing Standards







What does Prov Need?








Cloud & Premise



Presentations & Productions



Economical for Today



Ready for Tomorrow



The Basics





Established

ST 2110 and NMOS: Thousands of deployed devices



Open API

Registration & Discovery, Registry or P2P, Control



SD \rightarrow 32K, JPEG-XS, EDID/HPD Compression, Uncompressed



Oath2, HTTPS, and HDCP 2.3





Based on ST 2110 (Elementary) UDP, RTP, 1-100+ GbE

Multicast & Unicast,

Optional PTP, Asynchronous and Synchronous



AES 67, Common Pro AV & Consumer Formats



USB/KVM, CEC, Serial, GPIO Extension

JT-NM Pro AV Roadmap (not official, see official version on the <u>JT-NM website</u>)



	in progress	phase 1	phase 2
control	 Discovery, Registration, Connections NMOS IS-04 Dynamic Connections NMOS IS-05 & 07, Receiver Capabilities, EDID / HPD 	Network Services and Node Behavior ProAV version of TR-1001-1 Audio channel mapping NMOS IS-08 Support for Legacy Integration ARC, CEC, IR Remotes, GPIO, RS-232 Network addressing IPv4/IPv6	Training and Certification Curriculum and AVIXA Renewal Credits Device / Content Control Open, public control framework USB – HID Registration, Discovery, and Connection with support for Touch Screens
media	 Uncompressed Video & Audio ST 2110-20 & 30, AES67, AES3 Compressed Video Open, Freely Available CODEC Precise Timing SMPTE ST 2110-10, ST 2059 Simplified Timing VSF-TRxxx, Async & Relaxed timing 	Forward Error Correction VSF-TRxxx ProAV Audio Formats VSF-TRxxx	WAN & Internet Compression Codecs widely implemented in the AV over IP market WAN Error Correction Automated Return Request (RIST or SRT, tbd) Access Services (e.g. Closed Captioning) SMPTE ST 2110-40 or 41
security	Control Encryption NMOS IS-10	Copy protection HDCP 2.3, VSF-TRxxx Content Encryption VSF-TRxxx	secure by

Momentum for Open Standards AV over (P SHOWCASE





2018 Pro AV WG Starts ST2110 + NMOS + additional functions Integrated Systems Europe

(Feb 2020)

IP MEDIA EXPERIENCE IPMX brand launched at ISE 2020 Show AIMS Aliance for IP Media Solutions

 AIMS Pro AV Working Group dramatically increases promotion



 VSF and AMWA become involved in new technical specifications

MVGEMELT_®

joined AIMS (June 2020)





 More general acceptance of the need for IPMX by InfoComm 2021 attendees and exhibitors (Oct 2021)



joined AIMS (Mar, Aug 2021)

infocomm



Multi-vendor Interop at InfoComm 2022 (June 2022)



joined VSF (Feb 2022)

BARCOjoined AIMS

(Apr 2022)



Okay, what are the differences? What about live production?

The Differences that Lower Cost



	ST 2110 networked media NMOS open specifications	IP MEDIA EXPERIENCE
2110-20 Uncompressed	Optional, Typical	Optional
2110-22 with JPEG-XS	Optional	Optional , Baseline
Precision Time Protocol (PTP)	Required, ST 2059-1 & 2	Optional reduced accuracy & request interval minimums
RTCP Sender Reports		Required for async sources
Wide Sender (-21 Type W)	Optional	Required

The Tweaks & Additions



	ST 2110 networked media NMOS open specifications	IP MEDIA EXPERIENCE
YUV 4:2:2	Assumed	Required
RGB 4:4:4	Optional	Required
Audio	2110-30 (AES76)	2110-30 (AES76)
48, 44.1 & 96 kHz audio	Optional, Optional, Optional	Required, Should, Should
NMOS (IS 04, 05)	Optional	Required
IS-11 (EDID and Dynamic Connections)	Optional	Optional
HDCP 2.3 Support (HKEP)	_	Optional

What does it mean for live production? (IP SHOWCASE



- Supports synchronous and asynchronous sources directly.
 - Add asynchronous devices to a synchronous production and retain timing info.
 - Helps manage latency within the system.
- PTP that is easier to deploy
 - Similar to AES67 requirements. Low-cost switch and device compatible
- NMOS as the baseline control protocol grantees universal discovery and registration
 - EDID (IS-11) Support useful for like multiviewers
- KVM support is useful for supporting controller interfaces
- JPEG-XS as the baseline codec (TR-10-11 IPMX Compressed Video)
 - Near-perfect 4K60 4:2:2 over 1GbE
 - Subframe latency
 - Very low CPU/GPU usage
 - Other codecs supported
- Delivers software-friendly live production
- Retains interoperability with ST 2110

Any Questions?

Andrew Starks















Slide no bullets







Content – no bullets.

Slide with bullets



- Bullet 1
- Bullet 2
 - Bullet 3
 - Bullet 4





Replace text box with image

Image caption if required.

Delete text box if not required.